

# Iso-Dryer

- The ISO-Dryer was designed for optimum production, low maintenance, and versatility. The unit was originally designed as a component of a complete cut, wash, and dry system; eliminating the transfer of product from one container to another, thereby minimizing damage caused by unnecessary product moves. The simplified design allows easy access to all mechanical components (with complete disassembly possible in as little as as ten minutes). All components are off-the-shelf, supporting a quick turnaround.

- **CUSTOMIZED, VARIABLE SPEEDS**

- The ISO-Dryer's control panel has a three-position selector switch for 700, 800 or 900 rpm speed selection. Or ask us to customize the settings for your specific needs.

- **Solidly built to perform for the long run**

- The Dryer's isolation system is designed to absorb much of the centrifugal shock load, ensuring smooth operation and long bearing life.
- Electronic components are UL, CUL and CE approved.
- Electronic acceleration and braking ensure increased production through short startup and shutdown times - and eliminate the expense of replacing mechanical brakes.
- The Dryer is constructed of stainless steel to withstand wear and tear in the toughest environments.
- Washdown duty motor, gas assist shocks and hermetically sealed non-contact safety interlock switches are standard components.

- **SPECIFICATIONS**

- Height 44"
- Diameter 44"
- Basket Standard White 32 gal. Brute
- Weight 700 lbs.
- Motor 3-hp 208/230/460 (Must Specify 50/60 Hertz 1-Phase or 3-Phase)



## *TS Designs Inc.*



945 West 13th Street  
Burley, ID 83318  
Phone: **(208) 878-3000**  
Fax: (208) 878-3005  
E-Mail: [info@tsdesigns.org](mailto:info@tsdesigns.org)  
Web: [www.tsdesigns.org](http://www.tsdesigns.org)

